



SPECIFICATIONS	Laser Scanner		CMOS Imager	
	<b>Physical Characteristics</b>			
Dimensions (W x H x D)	36 x 85 x 19 mm / 1.4 x 3.3 x 0.7 inch			
Weight	Excluding battery: 38g / Including standard battery: 54g			
Notification	LED flash, Beep sound			
Input	Scan, Cancel button, Power switch			
Standard Battery	Rechargeable, 3.7V, 720mAh, Li-ion 15,000 scans per charge			
<b>Performance Characteristics</b>				
CPU	S3C2440A40, 400MHz			
OS	Linux	Windows CE 5.0		
Memory	16MB RAM / 32MB ROM Storage capacity 100,000 data			
Interface	RS-232C, USB 1.1 Client			
<b>User Environment Characteristics</b>				
Operating Temp	-5°C to 40°C / 23°F to 104°F			
Storage Temp	-30°C to 60°C / -22°F to 140°F			
Humidity	95% non-condensing			
Drop Spec	5ft. / 1.5m drop to steel surface, 2drops per 6 sides			
Rain/Dust Protection	IP30			
<b>Integrated Radio</b>				
WPAN Radio	Bluetooth Class II V1.2			
<b>Data Capture</b>				
Barcode Scanner	1D&PDF417 Laser Class II		1D&2D CMOS Imager	